# U3-3566XLE-C-HQ Rev.1.1 (1007535)


**Discontinued**
The model has been discontinued.



## Specification

### Sensor

| | |
|---|---|
| Sensor type | CMOS Color |
| Shutter | Global Shutter |
| Sensor characteristic | Linear |
| Pixel Class | 2 MP |
| Resolution | 2.30 Mpix |
| Resolution (h x v) | 1920 x 1200 Pixel |
| Aspect ratio | 16:10 |
| ADC | 10 bit |
| Color depth (camera) | 10 bit |
| Optical sensor class | 1/2.6" |
| Optical Size | 5.760 mm x 3.600 mm |
| Optical sensor diagonal | 6.79 mm 1/2.6" |
| Pixel size | 3 µm |
| CRA (Chief Ray Angle) | 0 ° |
| Manufacturer | Onsemi |
| Sensor Model | AR0234CSSC00SUKA0 |
| Gain (master/RGB) | 16x/8x |
| AOI horizontal | same frame rate |
| AOI vertical | increased frame rate |
| AOI image width / step width | 48 / 12 |
| AOI image height / step width | 4 / 2 |
| AOI position grid (horizontal/vertical) | 4 / 2 |
| Binning horizontal | same frame rate |
| Binning vertical | increased frame rate |
| Binning method | - |
| Binning factor | 2x2 |
| Decimation (subsampling) horizontal | same frame rate |
| Decimation (subsampling) vertical | increased frame rate |
| Decimation (subsampling) method | - |







IDS Imaging Development Systems GmbH
Dimbacher Str. 10 · 74182 Obersulm · Germany · Phone +49 7134 96196-0 · E-mail info@ids-imaging.com

## Model

| | |
|---|---|
| Frame rate freerun mode | 102 fps |
| Frame rate trigger (continuous) | 72 fps |
| Frame rate trigger (maximum) | 72 fps |
| Exposure time (minimum - maximum) | 0.012 ms - 2000 ms |
| Power consumption | 0.5 W - 1 W |
| Image memory | - |

## Ambient conditions

The temperature values given below refer to the outer device temperature of the camera housing.

| | |
|---|---|
| Allowed device temperature during operation | 0 °C - 55 °C / 32 °F - 131 °F |
| Allowed ambient temperature during storage | -20 °C - 80 °C / -4 °F - 176 °F |
| Humidity (relative, non-condensing) | 20 % - 80 % |

## Connectors

| | |
|---|---|
| Interface connector | USB Type-C |
| I/O connector | - |
| Power supply | USB cable |

## Design

| | |
|---|---|
| Lens Mount | S-Mount |
| IP code | IP30 |
| Dimensions H/W/L | 47.0 mm x 46.0 mm x 25.0 mm |
| Mass | 36 g |
| Housing material | Plastic |

## Features

List of on-camera image pre-processing features.
All features of the table are available via our IDS peak software for image pre-processing on the host computer (sensor model dependent).

| | | |
|---|---|---|
| Image Acquisition | Freerun | ✓ |
| | Software trigger | ✓ |
| | Hardware trigger | - |
| | Trigger controlled exposure | - |
| | Denoiser | - |
| | Long exposure | - |
| | Line scan | - |
| Flashing | Flashing | ✓ |
| | PWM flashing | - |
| Image Adjustments | Auto exposure | - |
| | Auto gain | - |
| | Auto whitebalance | - |
| | Color correction | - |
| | Gamma | - |
| | LUT | - |
| | Mirror/flip | X/Y |


IDS Imaging Development Systems GmbH
Dimbacher Str. 10 · 74182 Obersulm · Germany · Phone +49 7134 96196-0 · E-mail info@ids-imaging.com

| | | |
|---|---|---|
| On-board Image Processing | Pixel formats | BayerGR8<br>BayerGR10g40IDS |
| | Region of interest | ✓ |
| | Decimation (FPGA) | - |
| | Decimation (Sensor) | (2,4)x(2,4) |
| | Binning (FPGA) | - |
| | Binning (Sensor) | 2x2<br>Increases frame rate. |
| Others | Chunks | - |
| | Sequencer | - |
| | Events | - |
| | Firmware update | ✓ |
| | 1st supported firmware version | 2.9 |



IDS Imaging Development Systems GmbH
Dimbacher Str. 10 · 74182 Obersulm · Germany · Phone +49 7134 96196-0 · E-mail info@ids-imaging.com