# UI-2250SE-M-DL (AB.0010.1.10400.25)

**Discontinued**
The model has been discontinued.






## Specification

### Sensor

| | |
|---|---|
| Sensor type | CCD Mono |
| Shutter | Global Shutter |
| Sensor characteristic | Linear |
| Readout mode | Progressive scan |
| Pixel Class | 1.9 MP |
| Resolution | 1.92 Mpix |
| Resolution (h x v) | 1600 x 1200 Pixel |
| Aspect ratio | 4:3 |
| ADC | 12 bit |
| Color depth (camera) | 8 bit |
| Optical sensor class | 1/1.8"" |
| Optical Size | 7.040 mm x 5.280 mm |
| Optical sensor diagonal | 8.8 mm (1/1.82") |
| Pixel size | 4.4 µm |
| Manufacturer | Sony |
| Sensor Model | ICX274AL |
| Gain (master/RGB) | 13.8x/- |
| AOI horizontal | same frame rate |
| AOI vertical | increased frame rate |
| AOI image width / step width | 320 / 4 |
| AOI image height / step width | 240 / 1 |
| AOI position grid (horizontal/vertical) | 1 / 1 |
| Binning horizontal | - |
| Binning vertical | increased frame rate |
| Binning method | Mono |
| Binning factor | 2 / 3 / 4 |
| Subsampling horizontal | - |
| Subsampling vertical | increased frame rate |
| Subsampling method | Color |
| Subsampling factor | 2, 4 |






IDS Imaging Development Systems GmbH
Dimbacher Str. 10 · 74182 Obersulm · Germany · Phone +49 7134 96196-0 · E-mail info@ids-imaging.com

## Model

| | |
|---|---|
| Pixel clock range | 5 MHz - 30 MHz |
| Frame rate freerun mode | 12 |
| Frame rate trigger (maximum) | 12 |
| Exposure time (minimum - maximum) | 0.096 ms - 1572 ms |
| Power consumption | 1 W - 2.4 W |

## Ambient conditions

The temperature values given below refer to the outer device temperature of the camera housing.


| | |
|---|---|
| Device temperature during operation | 0 °C - 55 °C / 32 °F - 131 °F |
| Device temperature during storage | -20 °C - 60 °C / -4 °F - 140 °F |
| Humidity (relative, non-condensing) | 20 % - 80 % |

## Connectors

| | |
|---|---|
| Interface connector | USB 2.0 mini-B, screwable |
| I/O connector | 9-pin micro D-Sub socket (MPE Garry 11-0021-50-09L) |
| Power supply | USB cable |

## Pin assignment I/O connector

| | |
|---|---|
| 1 | Flash output with optocoupler (-) |
| 2 | Trigger input with optocoupler (+) |
| 3 | Shielding |
| 4 | USB Power supply (VCC) 5 V |
| 5 | USB Ground (GND) |
| 6 | Flash output with optocoupler (+) |
| 7 | Trigger input with optocoupler (-) |
| 8 | USB data (+) |
| 9 | USB data (-) |





Camera rear view


## Design


| | |
|---|---|
| Lens Mount | C-Mount |
| IP code | IP30 |
| Dimensions H/W/L | 34.0 mm x 32.0 mm x 48.3 mm |
| Mass | 79 g |





IDS Imaging Development Systems GmbH
Dimbacher Str. 10 · 74182 Obersulm · Germany · Phone +49 7134 96196-0 · E-mail info@ids-imaging.com





IDS Imaging Development Systems GmbH
Dimbacher Str. 10 · 74182 Obersulm · Germany · Phone +49 7134 96196-0 · E-mail info@ids-imaging.com