


Discontinued
The model has been discontinued.



Specification

Sensor	
Sensor type	CCD Mono
Shutter	Global Shutter
Sensor characteristic	Linear
Readout mode	Progressive scan
Pixel Class	1.9 MP
Resolution	1.92 Mpix
Resolution (h x v)	1600 x 1200 Pixel
Aspect ratio	4:3
ADC	12 bit
Color depth (camera)	8 bit
Optical sensor class	1/1.8"
Optical Size	7.040 mm x 5.280 mm
Optical sensor diagonal	8.8 mm (1/1.82")
Pixel size	4.4 µm
Manufacturer	Sony
Sensor Model	ICX274AL
Gain (master/RGB)	13.8x/-
AOI horizontal	same frame rate
AOI vertical	increased frame rate
AOI image width / step width	320 / 4
AOI image height / step width	240 / 1
AOI position grid (horizontal/vertical)	1 / 1
Binning horizontal	-
Binning vertical	increased frame rate
Binning method	Mono
Binning factor	2 / 3 / 4
Subsampling horizontal	-
Subsampling vertical	increased frame rate
Subsampling method	Color
Subsampling factor	2, 4



Model

Pixel clock range	5 MHz - 30 MHz
Frame rate freerun mode	12
Frame rate trigger (maximum)	12
Exposure time (minimum - maximum)	0.096 ms - 1572 ms
Power consumption	1 W - 2.4 W

Ambient conditions

The temperature values given below refer to the outer device temperature of the camera housing.


Device temperature during operation	0 °C - 55 °C / 32 °F - 131 °F
Device temperature during storage	-20 °C - 60 °C / -4 °F - 140 °F
Humidity (relative, non-condensing)	0 % - 100 %

Connectors

Interface connector	USB 2.0 mini-B, screwable
I/O connector	4-pin Binder socket (Binder series 712: 09-0412-20-04)
Power supply	USB cable

Pin assignment I/O connector

1	Trigger input with optocoupler (+)
2	Trigger input with optocoupler (-)
3	Flash output with optocoupler (-)
4	Flash output with optocoupler (+)



Camera rear view

Design

Lens Mount	C-Mount
IP code	IP65/67
Dimensions H/W/L	41.0 mm x 41.0 mm x 55.5 mm
Mass	175 g

