


Discontinued
The model has been discontinued.



Specification

Sensor	
Sensor type	CCD Mono
Shutter	Global Shutter
Sensor characteristic	Linear
Readout mode	Progressive scan
Pixel Class	0.3 MP
Resolution	0.31 Mpix
Resolution (h x v)	640 x 480 Pixel
Aspect ratio	4:3
ADC	12 bit
Color depth (camera)	8 bit
Optical sensor class	1/3"
Optical Size	4.736 mm x 3.552 mm
Optical sensor diagonal	5.92 mm (1/2.7")
Pixel size	7.4 µm
Manufacturer	Sony
Sensor Model	ICX424AL
Gain (master/RGB)	18x/-
AOI horizontal	same frame rate
AOI vertical	increased frame rate
AOI image width / step width	16 / 4
AOI image height / step width	120 / 1
AOI position grid (horizontal/vertical)	1 / 1
Binning horizontal	-
Binning vertical	increased frame rate
Binning method	Mono
Binning factor	2 / 3 / 4
Subsampling horizontal	-
Subsampling vertical	-
Subsampling method	-
Subsampling factor	-



Model

Pixel clock range	5 MHz - 30 MHz
Frame rate freerun mode	75
Frame rate trigger (maximum)	69
Exposure time (minimum - maximum)	0.044 ms - 638 ms
Power consumption	1 W - 1.9 W

Ambient conditions

The temperature values given below refer to the outer device temperature of the camera housing.


Device temperature during operation	0 °C - 55 °C / 32 °F - 131 °F
Device temperature during storage	-20 °C - 60 °C / -4 °F - 140 °F
Humidity (relative, non-condensing)	20 % - 80 %

Connectors

Interface connector	USB 2.0 mini-B, screwable
I/O connector	9-pin micro D-Sub socket (MPE Garry 11-0021-50-09L)
Power supply	USB cable

Pin assignment I/O connector

1	Flash output with optocoupler (-)
2	Trigger input with optocoupler (+)
3	Shielding
4	USB Power supply (VCC) 5 V
5	USB Ground (GND)
6	Flash output with optocoupler (+)
7	Trigger input with optocoupler (-)
8	USB data (+)
9	USB data (-)



Camera rear view

Design

Lens Mount	C-Mount
IP code	IP30
Dimensions H/W/L	34.0 mm x 32.0 mm x 48.3 mm
Mass	79 g

