


Discontinued
The model has been discontinued.



Specification

Sensor	
Sensor type	CMOS Color
Shutter	Rolling shutter
Sensor characteristic	Linear
Readout mode	Progressive scan
Pixel Class	1.9 MP
Resolution	1.92 Mpix
Resolution (h x v)	1600 x 1200 Pixel
Aspect ratio	4:3
ADC	8 bit
Color depth (camera)	12 bit
Optical sensor class	1/3"
Optical Size	4.480 mm x 3.360 mm
Optical sensor diagonal	5.6 mm (1/2.86")
Pixel size	2.8 µm
Manufacturer	Onsemi
Sensor Model	MT9D131STC
Gain (master/RGB)	5.8x/3.1x
AOI horizontal	increased frame rate
AOI vertical	increased frame rate
AOI image width / step width	32 / 4
AOI image height / step width	4 / 2
AOI position grid (horizontal/vertical)	4 / 2
Binning horizontal	increased frame rate
Binning vertical	increased frame rate
Binning method	Color
Binning factor	2
Subsampling horizontal	increased frame rate
Subsampling vertical	increased frame rate
Subsampling method	Color
Subsampling factor	2, 4, 8, 16



Model

Pixel clock range	3 MHz - 56 MHz
Frame rate freerun mode	23
Frame rate trigger (maximum)	23
Exposure time (minimum - maximum)	0.029 ms - 21376 ms
Power consumption	2.4 W - 3.4 W
Image memory	60 MB

Ambient conditions

The temperature values given below refer to the outer device temperature of the camera housing.


Device temperature during operation	0 °C - 55 °C / 32 °F - 131 °F
Device temperature during storage	-20 °C - 60 °C / -4 °F - 140 °F
Humidity (relative, non-condensing)	0 % - 100 %

Connectors

Interface connector	GigE RJ45, screwable
I/O connector	7-pin Binder connector (Binder series 712: 09-0423-020-07)
Power supply	12 V - 24 V

Pin assignment I/O connector

1	Trigger input with optocoupler (+)
2	Power supply (VCC)
3	Shielding
4	Ground (GND)
5	Flash output with optocoupler (+)
6	Flash output with optocoupler (-)
7	Trigger input with optocoupler (-)



Camera rear view

Design

Lens Mount	C-Mount
IP code	IP65/67
Dimensions H/W/L	41.0 mm x 53.0 mm x 42.7 mm
Mass	175 g

