


# U3-3002SE-M (AB02372)

Not recommended for new designs
The camera model is no longer recommended for new application development.








## Specification

### Sensor

| | |
|---|---|
| Sensor type | CMOS Mono |
| Shutter | Global Shutter |
| Sensor characteristic | Linear |
| Pixel Class | 12 MP |
| Resolution | 12.29 Mpix |
| Resolution (h x v) | 4096 x 3000 Pixel |
| Aspect ratio | 4:3 |
| ADC | 12 bit |
| Color depth (camera) | 12 bit |
| Optical sensor class | 1.1" |
| Optical Size | 14.159 mm x 10.371 mm |
| Optical sensor diagonal | 17.55 mm 1.1" |
| Pixel size | 3.45 µm |
| CRA (Chief Ray Angle) | 0 ° |
| Manufacturer | Sony |
| Sensor Model | IMX253LLR-C |
| Gain (master/RGB) | 24x/4x |
| AOI horizontal | same frame rate |
| AOI vertical | increased frame rate |
| AOI image width / step width | 264 / 8 |
| AOI image height / step width | 1 / 1 |
| AOI position grid (horizontal/vertical) | 8 / 1 |
| Binning horizontal | increased frame rate |
| Binning vertical | increased frame rate |
| Binning method | Horizontal: addition / Vertical: addition |
| Binning factor | 2x2 |
| Decimation (subsampling) horizontal | same frame rate |
| Decimation (subsampling) vertical | same frame rate |
| Decimation (subsampling) method | M/C automatic |





IDS Imaging Development Systems GmbH
Dimbacher Str. 10 · 74182 Obersulm · Germany · Phone +49 7134 96196-0 · E-mail info@ids-imaging.com

## Model

| | |
|---|---|
| Frame rate freerun mode | 32 fps |
| Frame rate trigger (continuous) | 32 fps |
| Frame rate trigger (maximum) | 37 fps |
| Exposure time (minimum - maximum) | 0.032 ms - 2000 ms |
| Long exposure (maximum) | 44000 ms |
| Line rate freerun mode (line scan) | 2750 1/s |
| Line rate trigger mode (line scan) | 2750 1/s |
| Lines per frame (line scan) | 8000 |
| Power consumption | 1.7 W - 4.3 W |
| Image memory | 128 MB |

## Ambient conditions

For PCB versions, refer to the separate hints in the respective documentation.

| | |
|---|---|
| Allowed device temperature during operation | 0 °C - 55 °C / 32 °F - 131 °F |
| Allowed device temperature during storage | -20 °C - 60 °C / -4 °F - 140 °F |
| Humidity (relative, non-condensing) | 20 % - 80 % |

## Connectors

| | |
|---|---|
| Interface connector | USB Type-C |
| I/O connector | 8-pin Hirose connector (HR25-7TR-8PA(73)) |
| Power supply | USB cable |

## Pin assignment I/O connector

| | |
|---|---|
| 1 | Ground (GND) |
| 2 | Flash output with optocoupler (-) - Line 1 |
| 3 | General Purpose I/O (GPIO) 1, 3.3 V - Line 2 |
| 4 | Trigger input with optocoupler (-) - Line 0 |
| 5 | Flash output with optocoupler (+) - Line 1 |
| 6 | General Purpose I/O (GPIO) 2, 3.3 V - Line 3 |
| 7 | Trigger input with optocoupler (+) - Line 0 |
| 8 | Output supply voltage, 5 V (100 mA) |




## Design

| | |
|---|---|
| Lens Mount | No mount |
| IP code | - |
| Dimensions H/W/L | 29.5 mm x 40.0 mm x 25.0 mm |
| Mass | 22 g |
| Housing material | - |

## Features

List of on-camera image pre-processing features.
All features of the table are available via our IDS peak software for image pre-processing on the host computer (sensor model dependent).

| | | |
|---|---|---|
| Image Acquisition | Freerun | ✓ |
| | Software trigger | ✓ |
| | Hardware trigger | ✓ |
| | Trigger controlled exposure | ✓ |
| | Denoiser | ✓ |
| | Long exposure | ✓ |
| | Line scan | ✓ |


IDS Imaging Development Systems GmbH
Dimbacher Str. 10 · 74182 Obersulm · Germany · Phone +49 7134 96196-0 · E-mail info@ids-imaging.com

| | | |
|---|---|---|
| Flashing | Flashing | ✓ |
| | PWM flashing | ✓ |
| Image Adjustments | Auto exposure | ✓ |
| | Auto gain | ✓ |
| | Auto whitebalance | - |
| | Color correction | - |
| | Gamma | ✓ |
| | LUT | ✓ |
| | Mirror/flip | X/Y |
| On-board Image Processing | Pixel formats | Mono8<br>Mono10<br>Mono10p<br>Mono12<br>Mono12p |
| | Region of interest | ✓ |
| | Decimation (FPGA) | ✓ |
| | Decimation (Sensor) | - |
| | Binning (FPGA) | ✓ |
| | Binning (Sensor) | 2x2<br>Increases frame rate. |
| Others | Chunks | ✓ |
| | Sequencer | - |
| | Events | ✓ |
| | Firmware update | ✓ |
| | 1st supported firmware version | 2.0 |


IDS Imaging Development Systems GmbH
Dimbacher Str. 10 · 74182 Obersulm · Germany · Phone +49 7134 96196-0 · E-mail info@ids-imaging.com